



FIRST LETTER UPPER CASE 5"  
 LOWER CASE LETTERS 4"  
 SUFFIX & NUMBERS SPLIT 3" & 2"

**PRIVATE - THROUGH STREET**



FIRST LETTER UPPER CASE 5"  
 LOWER CASE LETTERS 4"  
 SUFFIX & NUMBERS SPLIT 3" & 2"

**PRIVATE - CUL-DE-SAC**

**STANDARD CONSTRUCTION NOTES FOR STREET NAME SIGNS**

1. ALL STREET SIGNS SHALL BE HI-INTENSITY DOUBLE-FACED EXTRUDED BLADES.
2. FIRST LETTER OF SUFFIX SHALL BE UPPERCASE WITH ALL REMAINING LETTERS TO BE LOWERCASE
3. ADDRESS NUMBERS FOR STREET NAME BLADES WILL BE PROVIDED AT A LATER DATE.
4. CONTRACTOR SHALL SUBMIT SHOP DRAWINGS FOR STREET NAME BLADES PRIOR TO FABRICATION.
5. STREET SIGN POSTS SHALL BE 12 FEET LONG, 4 FEET DRIVEN INTO THE GROUND.
6. SIGN POSTS FOR STREET NAME BLADES SHALL BE ROUND TUBULAR ALUMINUM OR HOT DIPPED GALVANIZED STEEL, OUTSIDE DIAMETER 2-3/8 INCHES, WALL THICKNESS 0.109 INCHES.
7. SIGN LOCATIONS SHALL BE STAKED BY THE ENGINEER AT THE TIME OF CONSTRUCTION.
8. ALL PRIVATE STREET NAME BLADES SHALL BE "BLUE" IN COLOR. LETTERING ON ALL STREET NAME BLADES SHALL BE HIGH INTENSITY, "WHITE" IN COLOR.



**STANDARD DETAILS**  
**STREET NAME BLADE SIGNS**  
**PRIVATE STREETS**



Last Revision:  
 June 2005

**COTTAGE GROVE, MINNESOTA**

City Plate No.  
**STR-22**